# Operating Instructions

## Simmons Yardage Master 800 Model 801445

### introduction

yards and meters, and is accurate to within one foot from a distance of 10 to over 800 yards. It can also measure speeds up to 400 mph. It's resistant to the elements and has built-in hunter or golfer. operation modes to ignore rain and close up objects like brush. It is virtually silent, is ultra-compact and is ideal for the The Simmons® Yardage Master 800 displays distance in feet,

#### Parts List

case Yardage Master device; 3-volt battery; hand strap; carry Operation

### Install battery: Turn the device upside-down and firmly push the battery compartment lid outward to pop open the battery compartment. Insert the supplied CR2 3-volt battery into the compartment in the orientation indicated by the illustration in the battery slot in the pack (with "+"

tab side down).

Do not install the battery backward. If these precautions are not followed, the battery may battery voids your Simmons warranty. explode, catch fire or leak. An improperly installed Note: Follow the battery manufacturer's precautions.

display. batteries are low, the low battery indicator is lit in the down firmly to snap the lid back into place. Slide the battery compartment lid into place and press When

- power on the unit. Turn on power to the device: Press Hange button to
- and hold the eyepiece up against your eyeglasses. if you wear eyeglasses: Holl down the rubber eyecup
- object comes into sharp focus. To focus on an object: Rotate the eyepiece until the
- the internal liquid crystal display (LCD). To take a range reading: Press the Range button to take a range measurement. The measurement is displayed on While taking the range measurement, two vertical bars

Range display. second is taken. button is held down, one measurement per Distance is displayed for 10 seconds.

While you are taking a range measurement, try to hold the Yardage Master steady and fixed on one object. If you keep moving the device about, Yardage Master may not display a true distance measurement.

be acquired, an elongated zero appears on the LCD. If the target is too close or too far, and the target cannot

### Range Specifications:

Minimum range:	(0 MPH to 409 MPH):	Maximum range for speed measurement	Maximum range to a golf flagpole:	Maximum range to a tree	Maximum range to a building:	Maximum range to a reflective street sign:
10 yards	305 yards		307 yards	593 yards	710 yards	800 yards

unit powers off automatically. Power Off: If no buttons are pressed for 10 seconds, the

### Operation Modes


To Change Modes: After pressing the Range button, press the Mode button repeatedly to cycle through the



Fig. 1: Rangefinder, side view



Fig. 3: Back view



currently selected. The following modes are available: One of the mode indicators is lit to show which mode is

- Normal Mode: This is the normal operating mode. The indicator is not lit in this mode.
- Maximum range is reduced in this mode. Rain Mode: Select this mode to filter out rain drops.
- automatically when a target is very reflective. REFL (Reflective): The Reflective indicator is turned on
- yards away. >150 (Greater than 150): Select this mode to force the Yardage Master to ignore targets that are closer than 150
- moving target. SPD (Speed): Use this mode to measure the speed of a

the Range button while aiming at a moving target, until the SPD indicator is lit. Then press and hold down To use the SPD mode: Keep pressing the Mode button

bars appear on the LCD. keeping the target in the crosshairs. Two and then four

at one second intervals. down the Range button, the measurement is updated displays in the currently selected units (see "CONF" below for more information). If you continue to hold After about one second, the speed measurement

CONF (Configuration): Use this mode to change the top of the display. units (both distance and speed) are turned on at the distance and speed measurement units. The current

To use the CONF mode: Keep pressing the Mode button until the CONF indicator is lit. Then press and desired measurement unit starts to blink start to blink. Keep pressing the Mode button until the distance measurement unit (meters, yards or feet) will hold down the Range button-the currently selected

desired speed measurement unit starts to blink. start to blink. Keep pressing the Mode button until the Then press the Range button again and the current measurement unit (kilometers/hour, etc.

Finally, press the range button to activate both the distance and speed selections.

### General Specifications

Weight: Magnification: Accuracy: 1.5" × 4" × 2.75" ± 1 fact 7.2 oz (w/battery)

00 Eye relief: Field of View: 10mm 310 ft @ 1000 yds (6°) Internal

Objective focal length: Exit pupil: 4mm

Battery type: Self-calibration 90mm Automatic

Audible noise: Battery Life: Good for 3600 ranges CR-2 3 volt lithium (included)

Units of measurement:

Water resistant

Distance: Kilometers/hour, Miles/hour Meters, Yards, Feet

Feet/second, Meters/second

Yards/second

Carry case and strap included

### Cautions and Warnings

not attempt to remove the covers. Warning! Service is not possible to the sealed housing. Do

hazardous radiation exposure. Caution: Use of controls or adjustments or performance of procedures other than those specified herein may result in

to be damaged. housing is not damaged. Cease usage if housing is found Visually inspect the rangefinder periodically to insure that

interior. aser Energy up to 0.66 uJ in a 25ns pulse is present in the

#### Warranty

Every Simmons® Yardage Master device is warranted by Simmons Optios ("Simmons") to be free of defects in materials and workmanship for a period of ONE YEAR from the date of original purchase in the U.S.A. and Canada. At its option, Simmons will replace the product found upon inspection by Simmons to be defective, provided the defective product is returned to Simmons, as explained below. This warranty applies to the original purchaser only and is non-transferable. Simmons products purchased outside North America are not included in this warranty, but are overned under separate warranties issued by Simmons international Distributors.

RGA Number Required: Prior to the return of any product, a Return Goods Authorization (RGA) number must be obtained from Simmons by calling (800) 626-3233. Each returned product must include a written statement detailing the nature of the claimed defect, as well as the owner's name, address, and phone BOURN

This warranty is not valid in cases where the product has been abused or mishandled, where unauthorized repairs have been attempted or performed, or where depreciation of the product is due to normal wear-and tear. Simmons specifically disclaims special, indirect, or consequential damages or lost profit, which may result from a breach of this warranty. Any implied warranties which cannot be disclaimed are hereby limited to a term of one year from the date of originai retail purchase

from state to state. Simmons reserves the right to change product specifications or to discontinue productions without prior notice. This warranty supersedes all previous Simmons rangefinder warranties. This warranty gives you specific rights. You may have other rights which vary

procedure Any return made in the U.S.A. under this limited warranty must follow this

#### Packaging:

as filters, etc. If possible, ship the product in its original packaging. Please be sure to wrap the package securely and use filement strapping tape on the outside of the package. Send only the product to be repaired. Please do not send accessory tlems, such

What to include with Your Product:

- A short note explaining the reasons you are sending the product in for
- Your daytime phone number The RGA Number

- An address for returning your product to you. (No PO boxes, please). A check or maney order in the amount of \$10 to cover shipping and handling

#### Shipping:

We recommend that you ship your product to us by a traceable parcel service. We also recommend that you insure your shipment against loss. Many carriers automatically insure packages up to a certain nominal amount, typically \$100. Please check to see if the insurance provided by the carrier is adequate to cover the replacement value of your product. If you live in the United states, your product should be sent, freight prepaid, to:

### Simmons Optics

Attn: Yardage Master Repair 6001 Oak Canyon frvine, CA 92618

If you have a question concerning use of the Yardage Master, calt the Simmons Customer Service Department at (800) 626-3233. Customer Service hours are 8:00 AM to 5:00 PM, Pacific Time, Monday through Friday.

® The name "Simmons" and the Simmons logo, are trademarks registered with the U.S. Trademark and Paterit Office and in principal countries throughout the

FCC/CE & Patent Pending

CLASS 1 LASER PRODUCT

IEC 60825-1:1993+A1:1997+A2:2001 EN 60825-1:1994+A11:1996+A2:2001

